



## Gulf Pride 4T Plus

### Premium 4-Stroke Motorcycle Oil

#### Product Description

**Gulf Pride 4T Plus** series are premium quality 4-stroke gasoline engine oils developed specifically to meet the special requirements of the latest high performance air cooled 4-stroke motorcycles. These oils are blended from superior quality high viscosity index base oils and specially selected performance additives to provide excellent protection for engine, gearbox and wet clutch used in 4-stroke motorcycles. They provide high degree of reliability even under severe operating conditions. Gulf Pride 4T Plus exceeds the requirements of API SL and JASO MA2 for 4-stroke motorcycle oils as well as those of leading global 4-stroke motorcycle manufacturers.

#### Features & Benefits

- Outstanding thermo-oxidative stability minimises high temperature deposit formation and controls oil thickening facilitating extended engine and oil life
- Exceptional anti-wear properties protect vital engine and gear components leading to reduced maintenance costs
- Optimised frictional properties eliminate wet clutch slippage leading to increased power / fuel economy and improved drivability
- Unique combination of detergents and dispersants provide excellent control on piston deposits leading to faster heat dissipation and longer engine life
- Excellent shear stability maintains viscosity under high temperature-high shear environment and provides improved wear protection
- Exceptional low volatility characteristics reduce oil consumption and hydrocarbon pollution
- Effective rust and corrosion inhibition property ensures longer life of critical engine components
- Fuel saving potential (SAE 10W-30)

#### Applications

- Recommended for new generation 4-stroke gasoline engines in high performance motorcycles of all leading global manufacturers

#### Specifications, Approvals & Typical Properties

| Meets the following Specifications |             | 10W-30         | 20W-40 |
|------------------------------------|-------------|----------------|--------|
| API SL                             |             | X              | X      |
| Has the following on File Status   |             |                |        |
| JASO MA2                           |             | X              | X      |
| Typical Properties                 |             |                |        |
| Test Parameters                    | ASTM Method | Typical Values |        |
| Viscosity @ 100 °C, cSt            | D 445       | 11.4           | 14.50  |
| Viscosity Index                    | D 2270      | 147            | 112    |
| Flash Point, °C                    | D 92        | 232            | 240    |
| Pour Point, °C                     | D 97        | -33            | -24    |
| TBN, mg KOH/g                      | D 2896      | 8.5            | 6.50   |
| Density @ 15°C, Kg/l               | D 1298      | 0.860          | 0.883  |
| Sulphated Ash, %wt                 | D 874       | 0.9            | 0.91   |

February 2008

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

[www.gulfoilltd.com](http://www.gulfoilltd.com)