



SAFETY DATA SHEET

Issuing Date: 07-27-2014

Revision Date: 07-27-2014

Version 1

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name Gulf Supreme Duty XLE, SAE 15W-40
Product Code(s) 02119/15W-40/2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Engine oil
Uses advised against Any other purpose.

1.3. Details of the supplier of the safety data sheet

Supplier

1.4. Emergency telephone number

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Contains Calcium di(alkyl(C20-C24, even numbered) branched)-methyl benzenesulfonate, Calcium long chain alkaryl sulphonate, Polyolefin polyamine succinimide May produce an allergic reaction.

2.2. Label Elements

Signal Word
None.

Hazard Statements

EUH208 - Contains Calcium di(alkyl(C20-C24, even numbered) branched)-methyl benzenesulfonate, Calcium long chain alkaryl sulphonate, Polyolefin polyamine succinimide May produce an allergic reaction.

2.3. Other hazards

No information available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.1. Substances / 3.2. Mixtures**

This product is a mixture. Health hazard information is based on its ingredients

Chemical Name	EC-No	CAS-No	Weight %	Classification (Reg. 1272/2008)	REACH Registration Number
Highly refined base oil (Viscosity >20.5 cSt @40°C)	-	-	50% - 100%	**	-
Polyolefin polyamine succinimide, borated	-	NOT AVAILABLE	1% - 2.5%	Aquatic Chronic 4 (H413)	no data available
Polyolefin polyamine succinimide	-	NOT AVAILABLE	1% - 2.5%	Skin Sens. 1 (H317) Aquatic Chronic 4 (H413)	no data available
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	272-028-3	68649-42-3	1% - 2.5%	Eye Dam. 1 (H318) Aquatic Chronic 2 (H411)	01-2119657973-23-xx xx
Polyolefin polyamine succinimide, polyol	-	NOT AVAILABLE	1% - 2.5%	Aquatic Chronic 4 (H413)	no data available
Calcium long chain alkaryl sulphonate	-	722503-69-7	0% - 1%	Skin Sens. 1 (H317) Aquatic Chronic 4 (H413)	no data available
Calcium di(alkyl(C20-C24, even numbered) branched)-methyl benzenesulfonate	-	722503-68-6	0% - 1%	Skin Sens. 1 (H317) Aquatic Chronic 4 (H413)	no data available

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.

See Section 15 for additional information on base oils.

** Substances for which there are Community workplace exposure limits.

Full text of H- and EUH-phrases: see section 16

SECTION 4: FIRST AID MEASURES**4.1. Description of first-aid measures****General advice**

May produce an allergic reaction. When symptoms persist or in all cases of doubt seek medical advice.

Inhalation

Move to fresh air.

Skin contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing before re-use. May cause an allergic skin reaction. If symptoms persist, call a physician.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice.
Protection of First-aiders	Use personal protective equipment. Avoid contact with skin, eyes and clothing.

4.2. Most important symptoms and effects, both acute and delayed

Main Symptoms May cause allergic skin reaction

4.3. Indication of immediate medical attention and special treatment needed

Notes to physician May cause sensitization of susceptible persons. Treat symptomatically.

SECTION 5: FIRE FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment., Use CO2, dry chemical, or foam, Water spray or fog, Cool containers / tanks with water spray

Extinguishing media which shall not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire

5.2. Special hazards arising from the substance or mixture

Special Hazard

Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). In the event of fire and/or explosion do not breathe fumes. This material creates a fire hazard because it floats on water. Combustible material.

Hazardous Decomposition Products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Special protective equipment for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ensure adequate ventilation. Use personal protective equipment. Avoid contact with skin, eyes and clothing.

Advice for non-emergency personnel

Material can create slippery conditions.

Advice for emergency responders For personal protection see section 8.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

6.3. Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Dike to collect large liquid spills.

6.4. Reference to other sections

See Section 8/12/13 for additional information

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Keep away from open flames, hot surfaces and sources of ignition. Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials

Oxidizing agents

7.3. Specific end uses

Recommended use Engine oil

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Chemical Name	European Union	The United Kingdom	France	Spain
Highly refined base oil (Viscosity >20.5 cSt @40°C)				VLA-EC: 10 mg/m ³ VLA-ED: 5 mg/m ³

Chemical Name	Austria	Switzerland	Poland	Ireland
Highly refined base oil (Viscosity >20.5 cSt @40°C)				STEL: 10 mg/m ³ TWA: 5 mg/m ³ (Mist)

Chemical Name	Finland	Denmark	Norway	Sweden
Highly refined base oil (Viscosity >20.5 cSt @40°C)	TWA: 5mg/m ³ (Öljysumu)	TWA: 1 mg/m ³ (Olietåge)	TWA: 1 mg/m ³ (Oljetåke)	LLV: 1 mg/m ³ STV: 3 mg/m ³ (Oljedimma)

Derived No Effect Level (DNEL)

Workers Systemic toxicity

Workers Local effects

Consumers Systemic toxicity

Consumers Local effects

Predicted No Effect Concentration (PNEC)

8.2. Exposure controls

Engineering Measures Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye Protection

Safety glasses with side-shields.

Hand Protection

Protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Skin and body protection

Long sleeved clothing.

Respiratory protection

No special protective equipment required. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

Hygiene measures

Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product.

Environmental Exposure Controls

No special environmental precautions required.

Thermal hazards

None under normal use conditions

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state @20°C
Odor

liquid
Hydrocarbon-like

Appearance
Odor Threshold

clear amber
Not Applicable

Property

Values

Note

pH

No information available.

Melting/freezing point

No information available

Boiling point/boiling range	No information available	
Flash Point	230 °C / 446 °F	ASTM D 92
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limits in Air		
upper flammability limit	No information available	
lower flammability limit	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Relative density	0.8791	@15°C
Solubility(ies)	Insoluble in water	
Partition coefficient: n-octanol/water	Not Applicable	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Viscosity, kinematic	113.7 cSt @ 40 °C	ASTM D 445
Explosive properties	Not Applicable	
Oxidizing Properties	Not Applicable	

9.2 Other information

Viscosity, kinematic (100°C)	14.9 cSt @ 100°C	ASTM D 445
Pour point	-30 °C / -22 °F	ASTM D 97
VOC Content	No information available	

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None under normal use conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None under normal use conditions

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition

10.5. Incompatible Materials

Oxidizing agents

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Product Information - Principle Routes of Exposure

Inhalation	None known
Eye contact	None known
Skin contact	Repeated or prolonged skin contact may cause allergic reactions with susceptible persons
Ingestion	None known

Acute toxicity - Product Information

Product does not present an acute toxicity hazard based on known information.

Acute toxicity - Component Information

Chemical Name	LD50 Oral (Rat)	LD50 Dermal (Rat/Rabbit)	LC50 Inhalation
Highly refined base oil (Viscosity >20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	

Skin corrosion/irritation	None known.
Serious eye damage/eye irritation	None known.
Sensitization	
Respiratory Sensitization	None known.
Skin sensitization	May cause an allergic skin reaction.
Germ Cell Mutagenicity	None known.
Carcinogenicity	None known.
Repeated Dose Toxicity	None known.
Reproductive toxicity	None known.
Specific target organ systemic toxicity (single exposure)	None known.
Specific target organ systemic toxicity (repeated exposure)	None known.
Aspiration hazard	None known.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects No special environmental measures are necessary.

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts		1.0 - 5.0: 96 h Pimephales promelas mg/L LC50 static 10.0 - 35.0: 96 h Pimephales promelas mg/L LC50 semi-static		1 - 1.5: 48 h Daphnia magna mg/L EC50
---	--	--	--	--

12.2. Persistence and degradability

The product is not readily biodegradable, but it can be degraded by micro-organisms, it is regarded as being inherently biodegradable.

12.3. Bioaccumulative potential

No information available

12.4. Mobility in soil

The product is insoluble and floats on water

12.5. Results of PBT and vPvB assessment

This preparation contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This preparation contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

12.6. Other adverse effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues / Unused Products

Dispose of as hazardous waste in compliance with local and national regulations

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Observe all label precautions until container is cleaned, reconditioned or destroyed.

Other Data

According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: TRANSPORT INFORMATION

14.1. UN-Number

Not regulated

14.2. UN proper shipping name

Not regulated

14.3. Transport hazard class

Not regulated

14.4. Packing group

Not regulated

14.5. Environmental Hazards

None

14.6. Special precautions for users

None

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

IMDG/IMO Not regulated**ADR/RID** Not regulated**ICAO/IATA** Not regulated**SECTION 15: REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

The Classification, Labeling and Packaging of Substances and Mixtures (CLP) Regulation (EC 1272/2008)
 Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

The highly refined base oil (Viscosity >20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical Name	CAS-No	EC-No	REACH Registration Number
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8	01-2119488706-23-xxxx
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	265-091-3	01-2119487081-40-xxxx
Residual oils (petroleum), solvent deasphalted	64741-95-3	265-096-0	01-2119487081-40-xxxx
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	265-097-6	01-2119483621-38-xxxx
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5	265-098-1	01-2119480374-36-xxxx
Residual oils (petroleum), solvent-refined	64742-01-4	265-101-6	01-2119488707-21-xxxx
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0	01-2119467170-45-xxxx
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6	01-2119480375-34-xxxx
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1	01-2119484627-25-xxxx
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7	01-2119487077-29-xxxx
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	265-159-2	01-2119480132-48-xxxx
Residual oils (petroleum), hydrotreated	64742-57-0	265-160-8	01-2119489287-22-xxxx
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	265-161-3	
Residual oils (petroleum), solvent-dewaxed	64742-62-7	265-166-0	01-2119480472-38-xxxx
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7	01-2119471299-27-xxxx
Paraffin oils (petroleum), catalytic dewaxed heavy	64742-70-7	265-174-4	01-2119487080-42-xxxx
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8	265-176-5	01-2119485040-48-xxxx
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7	276-735-8	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9	276-736-3	01-2119555262-43-xxxx

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	276-737-9	01-2119474878-16-xxxx
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	276-738-4	01-2119474889-13-xxxx
Lubricating oils	74869-22-0	278-012-2	01-2119495601-36-xxxx
White mineral oil (petroleum)	8042-47-5	232-455-8	

15.2. Chemical Safety Assessment

No information available

SECTION 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

Repr.-Reproduction toxicity

Asp. Tox. - Aspiration Toxicity

Acute Tox. - Acute Toxicity

Aquatic Acute - Acute Aquatic Toxicity

Aquatic Chronic - Chronic Aquatic Toxicity

Eye Dam. - Eye Damage

Eye Irrit. - Eye Irritation

Skin Corr. - Skin Corrosion

Skin Irrit. - Skin Irritation

Skin Sens. - Skin Sensitizer

Resp. Sens. - Respiratory Sensitizer

STOT SE - Specific target organ systemic toxicity (Single exposure)

STOT RE - Specific target organ systemic toxicity (repeated exposure)

VOC - Volatile organic compounds

Full text of H-Statements referred to under sections 2 and 3

<ul style="list-style-type: none"> • H224 - Extremely flammable liquid and vapor • H225 - Highly flammable liquid and vapor • H226 - Flammable liquid and vapor • H270 - May cause or intensify fire; oxidizer • H271 - May cause fire or explosion; strong oxidizer • H272 - May intensify fire; oxidizer • H290 - May be corrosive to metals • H300 - Fatal if swallowed • H301 - Toxic if swallowed • H302 - Harmful if swallowed • H304 - May be fatal if swallowed and enters airways • H310 - Fatal in contact with skin • H311 - Toxic in contact with skin • H312 - Harmful in contact with skin • H314 - Causes severe skin burns and eye damage • H315 - Causes skin irritation • H317 - May cause an allergic skin reaction • H318 - Causes serious eye damage • H319 - Causes serious eye irritation • H330 - Fatal if inhaled • H331 - Toxic if inhaled • H332 - Harmful if inhaled • H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled • H335 - May cause respiratory irritation • H336 - May cause drowsiness or dizziness • H340 - May cause genetic defects 	<ul style="list-style-type: none"> • H341 - Suspected of causing genetic defects • H350 - May cause cancer • H351 - Suspected of causing cancer • H360 - May damage fertility or the unborn child • H361 - Suspected of damaging fertility or the unborn child • H362 - May cause harm to breast-fed children • H370 - Causes damage to organs • H371 - May cause damage to organs • H372 - Causes damage to organs through prolonged or repeated exposure • H373 - May cause damage to organs through prolonged or repeated exposure • H400 - Very toxic to aquatic life • H410 - Very toxic to aquatic life with long lasting effects • H411 - Toxic to aquatic life with long lasting effects • H412 - Harmful to aquatic life with long lasting effects • H413 - May cause long lasting harmful effects to aquatic life • H360Df - May damage the unborn child. Suspected of damaging fertility • H360D - May damage the unborn child • H360FD - May damage fertility. May damage the unborn child • H360F - May damage fertility • H361d - Suspected of damaging the unborn child • H361fd - Suspected of damaging fertility. Suspected of damaging the unborn child • H361f - Suspected of damaging fertility • EUH066 - Repeated exposure may cause skin dryness or cracking • EUH210 - Safety data sheet available on request • EUH208 - May produce an allergic reaction
---	--

Exposure scenario

No information available

Issuing Date: 07-27-2014

Revision Date: 07-27-2014

Revision Note Not Applicable.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.